

# Series DSS - CPWS

## Content Player Workstation



## Digital Signage Player Workstations

This Robust Digital Signage Player can handle the most Demanding Digital Signage Profiles with Plenty of Bandwidth to spare.

We have designed our CPWS to facilitate this process! It contains all the hardware and software needed to Play your Digital Signage Content.

The CPWS is loaded with Infocaster's Content Player software and the video output card required to display digital signage. It is designed to display attractive multi-zone layouts, Integrate crawls, rolls, animations, clocks, video and audio clips for dynamic presentations. It can also process live video & audio capture to bundle your message with current local/Cable/Sat content.

A single CPWS is all you need to provide either a single or multizone content to display screens positioned nearby. Utilizing optional Video distribution amplifier / splitter (DSS-VAS.X) with breakout cables (DSS-C.XX) and Audio Amplifier (DSS-AA300) easily enables the use of many displays screens and speakers in the same area, all providing identical content simultaneously.

The player software is constantly running a player monitor. The monitor will detect if the InfoCaster player is in a bad state, and will restart the InfoCaster software and play the page it was playing before the problem occurred. These kind of self diagnostic tools are designed to provide you with the peace of mind that the digital signage will constantly be available.

This player both hardware and software are designed to serve you & your customers content Day-in & Day-out for many years to come.

### Features

#### Hardware:

- Intel Motherboard
- Intel P4 3.2 Ghz Hyper-Threading, 800 Mhz FSB, 2 MB cache
- 2 Gb 667 memory Dual Channel DDR2
- 1 - OS & Program Drive (80 Gb)
- 1 - 80 Gb SATA 1.5 Content Drive
- Analog / Digital Audio Source
- ATI X800 Radeon PCI-X16 DVI-D /VGA, 256 MB
- Osprey Video / Audio Capture Card
- 350 W Micro ATX Power Supply
- Custom Cooling System
- 10/100/1000 Mhz NIC Card
- All Aluminum Chassis
- Small Form Factor

#### Software:

- Windows XP Professional
- Infocaster's Player Software

#### Options:

- DSS-VAS.X - Video distribution amplifier / splitter
- DSS-AA300 - Audio Amplifier
- DSS-C.XX - Breakout cables

Please feel free to consult with a Sales Engineer for additional information or visit our web site.



### Display Integration Technologies

1330 Specialty Dr, Suite A  
Vista, CA, 92081  
Phone 760.599.9225  
Fax 760.454.0328

www.DITHD.COM  
Sales@DITHD.com

