



SERIES DSS-FSP42

FREE STANDING 42" CONDITIONED NEMA 4 PEDESTAL

Features



42" Free Standing Pedestal Maximize Your Advertising Real Estate

The DSS-FSP42 Series is a high performance 42" LCD display which rounds out our DSS Series with the ultimate in All Weather and Solar conditions.

The DSS-FSP42 utilizes new technologies which reduce Image Sticking and the Yogore Effect for Public Displays.

This unit is built to take the heat with an operating temperature range from -4°F to 122°F with options of an operating temperature range of -40°F to 140°F.

These units have an optical bonded front lens with IR, UVa and UVb Protection against heat and optical front loading. Optional High-Brighted Unit can achieve 1000 NITS.

This Unit allows you to put your Digital Signage or Public Display where the people are "Outside"

The DSS-FSP42 is an all Aluminum construction solution with a Standard Finish of Tan Gloss Coat and medium texture, but it can be optionally customized to a variety of colors.

Enclosure / Pedestal:

- All Weather NEMA 4 (Optional NEMA 4X)
- All Aluminum Construction
- Mountable to optional movable base (As shown) or permanently to floor

Display:

- Solar Enhanced Daylight Viewable with Optically Bonded Lens
- 42" Diagonal Active Matrix TFT LCD Displays
- Full High Definition Panels (1920x1080p / 1366x768)
- 178° / 178° wide viewing Angle
- 1000:1 Contrast Ratio
- 600 NITS Brightness
- On Screen Display (OSD) Monitor Controls with wireless remote

Video Inputs:

- DVI, HDMI w/ Audio (Optional), HD component, VGA, S-Video and Composite - Supports all Major Video Formats

Other Features:

- The OHD-FSP comes standard with T1 Cooling which boasts a wide operating temperature range from 32° - 120°F and a storage range of -4°-140°F.
- Built in Audio amplifier

Options:

- Optional 52 & 65" LCD Sizes with custom sizes available from 26-82"+ LCD
- Optional External Audio Pre-Amp
- Optional Vandal Glass
- Optional IR Touch Screen
- Optional Base as shown
- Optional Securable Controls
- Optional 24 VDC Power
- Optional T2 Model with Heating, NEMA 4 (Operating range of -4°-122°F ambient temperature)
- Optional T3 Model with A/C (1200 BTU), NEMA 4X, and Operating range of 32°-128°F ambient temperature
- Optional T4 Model with A/C (1500 BTU), NEMA 4X, and Operating range of 32°-132°F ambient temperature
- Optional T5 Model with A/C (1800 BTU), NEMA 4X and Operating range of 32°-140°F ambient temperature
- Optional T6 Model, NEMA 4X, with both A/C (1800 BTU) and a heater and an Operating range of -40°-140°F.

Please refer to our OHD consumer line of products for LCD Sizes 42" & 52" and less demanding temperature specifications.

Please feel free to consult with a Sales Engineer for additional information or visit our web site.



Display Integration Technologies

1330 Specialty Dr, Suite A
Vista, CA, 92081
Phone 760.599.9225
Fax 760.454.0328

www.DSS.DITHD.COM
Sales@DITHD.com

